Heat and mass transfer: **2**, 141-147
Heat conduction: **1**, 7-20; **7**, 558-567; **8**, 617-625, 665-677
Heat exchanger: **2**, 128-140; **5**, 376-390; **8**, 626-638
Heat exchanger simulator: **8**, 626-638
Heat of dilution and dissolution: **4**, 272-283
Heat transfer: **1**, 7-20, 56-67; **2**, 89-104, 128-140; **3**, 149-164, 194-211, 237-247; **4**, 272-283; **5**, 362-375, 376-390, 408-419; **6**, 463-474, 475-485; **7**, 531-539
Heat transfer coefficient: **4**, 307-319; **7**, 540-550
Heat transfer enhancement: **5**, 408-419; **8**, 639-651, 652-664
Hemispherical reflectance: **2**, 76-88
High cooling performance: **3**, 226-236
HTOR: **8**, 665-677
Hybrid system: **8**, 617-625
Hydrogen bonding: **7**, 578-594

Ice storage: **1**, 21-27
Impingement duct: **3**, 226-236
Inclined plate: **5**, 362-375
Induction motor: **1**, 7-20
Industrial furnace: **5**, 391-407
Infrared radiation drying: **2**, 141-147
Infrared thermography: **8**, 617-625
Integral equation: **3**, 237-247
Interface temperature: **7**, 578-594
Interfacial structure: **4**, 257-271
Interfacial suction effect: **7**, 568-577
Inverse analysis: **3**, 165-181
Inverse solubility: **4**, 297-306

Large bubble: **4**, 307-319
Laser AC heating: **6**, 498-512
Laser pulse: **5**, 331-343
LiBr: **8**, 606-616
Liquid air: **4**, 284-296
Liquid film heat transfer model: **7**, 524-530
Liquid-vapor interface: **2**, 105-116
Lock-in technique: **6**, 498-512

Magnetic fluid: **2**, 69-75
Marangoni convection: **2**, 105-116
Mass transfer: **6**, 475-485
Measurement: **2**, 117-127
Microgravity: **2**, 105-116
Microlayer: **6**, 456-462; **7**, 578-594
Minimum fluidization air velocity: **4**, 307-319
Mixture: **8**, 595-605
Model: **7**, 551-557
Molecular potential energy: **2**, 69-75
Monte Carlo method: **5**, 391-407
Movable particles: **1**, 28-41
Multiphase flow: **2**, 128-140; **3**, 212-225; **5**, 376-390; **8**, 639-651, 652-664

N_2: **3**, 182-193
Natural convection: **1**, 56-67; **5**, 362-375, 408-419; **6**, 463-474, 486-497; **8**, 665-677
Non-Fickian effects: **1**, 1-6
Nuclear reactor: **8**, 665-677
Nucleate boiling: **1**, 28-41; **6**, 475-485
Numerical analysis: **2**, 89-104; **3**, 237-247; **6**, 438-455
Numerical simulation: **1**, 42-55; **4**, 284-296; **6**, 421-429

O_2: **3**, 182-193
Opposing flow: **5**, 362-375
Optical measurement: **6**, 498-512
Optimal control: **3**, 237-247

Parallel flow: **6**, 421-429
Phase change: **6**, 475-485
Pipe flow: **3**, 149-164
Plate: **5**, 408-419
Polymer electrolyte: **6**, 421-429
Polymer solution: **4**, 297-306
Pool boiling: **4**, 272-283; **7**, 578-594
Porous layer: **7**, 568-577
Porous media: **6**, 463-474
Pressure drop: **8**, 639-651, 652-664
Pressure loss: **5**, 376-390
Pulsating fluidized bed: **4**, 307-319

Quasi-steady: **6**, 486-497

R407C: **8**, 626-638
Radiation-convection heat transfer: **5**, 391-407
Radiation energy exchange: **2**, 76-88
Radiation heat transfer: **5**, 391-407
Radiation heating: **2**, 117-127
Real surface: **2**, 76-88
Redundancy: **3**, 226-236
Reflectance thermometry: **6**, 498-512
Refrigerant: **2**, 128-140; **5**, 376-390; **8**, 626-638
Refrigeration: **5**, 344-361

Scale deposits: **2**, 117-127
Secondary cells: **6**, 486-497

Seed: **2**, 141-147
Self-humidifying: **6**, 421-429
Semitransparent medium: **5**, 331-343
Shrinkage: **3**, 194-211
Similarity: **2**, 105-116
Slit jet: **3**, 226-236
Slug flow: **4**, 257-271
Solidification: **3**, 194-211
Spectroscopic measurement: **2**, 76-88
Speed of mass propagation: **1**, 1-6
Standpipe: **8**, 665-677
Static bed: **4**, 307-319
Steam absorption: **8**, 606-616
Stirling cooler: **5**, 344-361
Stirling cycle: **5**, 344-361
Stress: **3**, 194-211
Surface evaporation: **7**, 513-523
Surface roughness: **2**, 76-88
Surface tension: **2**, 69-75
Swelling liquid front: **4**, 257-271
Swirl: **8**, 639-651, 652-664

Taylor dispersion: **3**, 182-193
Temperature fluctuation: **7**, 578-594
Temperature response: **5**, 331-343
Temperature visualization: **3**, 165-181
Thermal contact conductance: **1**, 7-20; **6**, 498-512
Thermal convection loop: **6**, 430-437
Thermal network method: **2**, 128-140; **5**, 376-390
Thermal radiation: **2**, 76-88; **8**, 665-677
Thermal resistance: **2**, 117-127; **3**, 226-236; **7**, 558-567
Thermal room environment: **5**, 391-407
Thermochromic liquid crystal: **2**, 89-104
Thermodynamics: **4**, 320-330
Thermophysical properties: **2**, 76-88; **4**, 320-330
Thermophysical property: **3**, 182-193
Transient heat transfer: **5**, 331-343
Turbine blade: **2**, 89-104
Turbulent flow: **1**, 56-67
Two-pass: **2**, 141-147
Two-phase flow: **7**, 524-530

Vapor concentration: **8**, 595-605
Vapor explosion: **4**, 297-306
Vapor-gas mixtures: **7**, 531-539
Vaporization: **4**, 249-256
Vertical annulus: **6**, 486-497
Vertical parallel plate: **1**, 56-67
Vertical upward flow: **8**, 639-651, 652-664
Vibrated bed: **2**, 141-147
Void fraction: **4**, 257-271

Wake: **4**, 257-271
Water: **8**, 595-605
Water + ammonia mixture: **4**, 320-330
Water-ethanol: **6**, 475-485
Wettability: **6**, 456-462
Wire coil: **8**, 639-651, 652-664
Working fluid: **5**, 344-361

Zeotropic refrigerant mixture: **8**, 626-638
Zero-flux zone: **4**, 249-256